





LED Flood Light 50W / 70WCOB / 100W COB / 150W COB / 200W COB

Electrical Input Voltage AC 100-240V Frequency Power Factor Bulb Type LED Flood Optical Color Temperature Lumens Lumens 4500 / 6300 / 9000 / 13500 / 14000 CRI >80 Beam Angle Mechanical Wattages 50W, 70W, 100W, 150W, 200W Bulb Shape Base Type Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates cSA RoHS CE FCC Compliant SKU 50W 50W SX-FL-50 70W COB SX-FL-50 70W COB SX-FL-100COB 150W COB SX-FL-100COB 200W COB SX-FL-200COB	000 / 200		
Frequency Power Factor Bulb Type LED Flood Optical Color Temperature Lumens	Electrical		
Power Factor Bulb Type LED Flood Optical Color Temperature Lumens 4500 / 6300 / 9000 / 13500 / 14000 CRI >80 Beam Angle Mechanical Wattages 50W, 70W, 100W, 150W, 200W Bulb Shape Base Type Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm a 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates cSA RoHS CE FCC Compliant SKU SX-FL-50 70W COB SX-FL-50COB 150W COB SX-FL-150COB	Input Voltage	AC 100-240V	
Bulb Type LED Flood Optical Color Temperature 4500 / 6300 / 9000 / 13500 / 14000 Lumens 4500 / 6300 / 9000 / 13500 / 14000 CRI >80 Beam Angle	Frequency		
Optical Color Temperature 4500 / 6300 / 9000 / 13500 / 14000 CRI >80 Beam Angle	Power Factor		
Color Temperature 4500 / 6300 / 9000 / 13500 / 14000 CRI >80 Beam Angle ***Mechanical Wattages 50W, 70W, 100W, 150W, 200W Bulb Shape **Base Type Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm and 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates cSA RoHS CE FCC Compliant SKU SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Bulb Type	LED Flood	
Lumens 4500 / 6300 / 9000 / 13500 / 14000 CRI >80 Beam Angle *** Mechanical Wattages 50W, 70W, 100W, 150W, 200W Bulb Shape *** Base Type *** Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm a 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates CSA RoHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Optical		
CRI >80 Mechanical Wattages 50W, 70W, 100W, 150W, 200W Bulb Shape Base Type Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates cSA RoHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 150W COB SX-FL-100COB 150W COB SX-FL-150COB	Color Temperature		
Beam Angle Mechanical Wattages 50W, 70W, 100W, 150W, 200W Bulb Shape Base Type Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates CSA ROHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 150W COB SX-FL-100COB 150W COB SX-FL-150COB	Lumens	4500 / 6300 / 9000 / 13500 / 14000	
Mechanical Wattages 50W, 70W, 100W, 150W, 200W Bulb Shape Base Type Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates cSA RoHS CE FCC Compliant SKU SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	CRI	>80	
Wattages 50W, 70W, 100W, 150W, 200W Bulb Shape Base Type Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm and 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates cSA RoHS CE FCC Compliant SKU 50W 70W COB SX-FL-50 70W COB SX-FL-100COB 150W COB SX-FL-150COB	Beam Angle		
Bulb Shape Base Type Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78 / 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates cSA RoHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Mechanical		
Base Type -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates CSA ROHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Wattages	50W, 70W, 100W, 150W, 200W	
Temperature Range -40C to +55C Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm and 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates CSA RoHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Bulb Shape		
Material Aluminum and Toughened Glass Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates cSA RoHS CE FCC Compliant SKU 50W 70W COB SX-FL-50 70W COB SX-FL-70COB 150W COB SX-FL-100COB 150W COB SX-FL-150COB	Base Type		
Lifespan 40,000 hours Warranty 3 years Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates CSA RoHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Temperature Range	-40C to +55C	
Warranty 3 years Size 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates cSA RoHS CE FCC Compliant SKU 50W 70W COB SX-FL-50 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Material	Aluminum and Toughened Glass	
Size Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates CSA RoHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Lifespan	40,000 hours	
Dimensions 287x237x155mm / 290x360x220mm / 315x250x116mm 375x310x187mm / 400x340x192mm Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates CSA RoHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Warranty	3 years	
375x310x187mm / 400x340x192mm Net Weight 3.78 / 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates Certificates cSA RoHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Size		
Net Weight 3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg Certificates CSA RoHS CE FCC Compliant SKU 50W 50W COB SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Dimensions	287x237x155mm / 290x360x220mm / 315x250x116mm	
Certificates Certificates cSA RoHS CE FCC Compliant SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB		375x310x187mm / 400x340x192mm	
Certificates cSA RoHS CE FCC Compliant SKU 50W 50W COB SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Net Weight	3.78/ 4.55kg / 3.78kg / 6.5kg / 7.5kg	
SKU 50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB			
50W SX-FL-50 70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	Certificates	cSA RoHS CE FCC Compliant	
70W COB SX-FL-70COB 100W COB SX-FL-100COB 150W COB SX-FL-150COB	SKU		
100W COB SX-FL-100COB 150W COB SX-FL-150COB	50W	SX-FL-50	
150W COB SX-FL-150COB	70W COB	SX-FL-70COB	
	100W COB	SX-FL-100COB	
200W COB SX-FL-200COB	150W COB	SX-FL-150COB	
	200W COB	SX-FL-200COB	



LED Floodlights are the modern choice for lighting of various large areas such as parking lots, open and closed working sites, as well as for decorative lighting for buildings.

The main benefit of LED Floodlights is their energy saving feature, crucial for the cases when the light must be kept on for the whole night.

LED Floodlights are up to 10 times more economical than the older halogen floodlights, therefore, the investment made for their purchase will normally be paid back within 1 year. LED Floodlights have a lifetime greater than 5 times that of the older halogen floodlights.

The LED Floodlights have a high level of IP 65 protection, which allows for their use in various weather conditions on a warehouse, stadium, dock, landscape lighting, stage, building, billboard, etc.



kingers-supply.com