

## LED Rechargeable Flood Light 5W / 10W / 20W / \* / Tripod

Electrical	
Input Voltage	AC 110-240VAC and DC 12/24V
Frequency	
Power Factor	
Bulb Type	LED Flood
Charging Time	5 hours
Working Time	3 hours
Optical	
Color Temperature	
Lumens	450 / 900 / 1800 / * / *
CRI	>80
Beam Angle	
Mechanical	
Wattages	5W, 10W, 20W, * , *
Bulb Shape	
Base Type	
Temperature Range	-40C to +55C
Material	Aluminum and Toughened Glass
Lifespan	40,000 hours
Warranty	3 years
Li-ion Battery 7.4V	2.2Ah / 4.4Ah / 8.8Ah / * / *
Size	
Dimensions	
Net Weight	
Certificates	
Certificates	
SKU	
5W 3Hour Battery	SX-FLR3-5
10W 3Hour Battery	SX-FLR3-10
20W 3Hour Battery	SX-FLR3-20
?W 6-8Hour Battery	
Tripod (Single, twin, 3-head option, adjustable height)	SX-FLR-TRI



LED Floodlights are the modern choice for lighting of various large areas such as parking lots, open and closed working sites, as well as for decorative lighting for buildings. The main benefit of LED Floodlights is their energy saving feature, crucial for the cases when the light must be kept on for the whole night. LED Floodlights are up to 10 times more economical than the older halogen floodlights, therefore, the investment made for their purchase will normally be paid back within 1 year. LED Floodlights have a lifetime greater than 5 times that of the older halogen floodlights. The LED Floodlights have a high level of IP 65 protection, which allows for their use in various weather conditions on a warehouse, stadium, dock, landscape lighting, stage, building, billboard, etc.



**kingers-supply.com**

**sales@kingers-supply.com**    **Box 1237 Three Hills, AB, T0M2A0**    **403-861-0033**

**BULBS   FLOODS   HIGHBAY   PANEL LIGHTS   RETROFIT   STREET & PARKING LIGHTS   VAPOR PROOF LIGHTS   WALL PACK TUNNEL & CANOPY**