

| High-Bay | |
|---------------------|--------------------------------------|
| Replaces | HID lighting systems |
| Electrical | |
| Input Voltage | AC 100-277V |
| Frequency | 50-60Hz |
| Power Factor | >0.95 |
| Bulb Type | LED High Bay Series |
| Optical | |
| Lumens | 9000 / 13000 / 16640 / 25000 / 40480 |
| CRI | >70 |
| Beam Angle | 90° or 120° |
| Mechanical | |
| Wattages | 100W, 150W, 200W, 300W, 460W |
| Bulb Shape | |
| Base Type | E26 |
| Temperature Range | -30C to +60 C |
| Material | Aluminum and Toughened Glass |
| Lifespan | 50,000 hours |
| Warranty | 3 years |
| Size | |
| Dimensions | |
| Net Weight | |
| Certificates | |
| Certificates | cUL, CE, FCC, RoHS compliant |
| SKU | |
| 100W | SX-HB-100 |
| 150W | SX-HB-150 |
| 200W | SX-HB-200 |
| 300W | SX-HB-300 |
| 460W | SX-HB-460 |



Until recently, high-intensity discharge (HID) lighting systems were considered the only option for illuminating high-bay spaces.

Recent advances in LED lighting systems now make these systems more attractive choices for lighting spaces that have high ceilings.



kingers-supply.com

sales@kingers-supply.com

Box 1237 Three Hills, AB, T0M2A0

403-861-0033

BULBS FLOODS HIGHBAY PANEL LIGHTS RETROFIT STREET & PARKING LIGHTS VAPOR PROOF LIGHTS WALL PACK TUNNEL & CANOPY