

High-Bay 347 VAC	
Replaces	HID lighting systems
Electrical	
Input Voltage	AC 90-480V
Frequency	50-60Hz
Power Factor	>0.95
Bulb Type	LED High Bay Series
Optical	
Lumens	9000 / 13000 / 16640 / 27000
CRI	>70
Beam Angle	90° or 120°
Mechanical	
Wattages	100W, 150W, 200W, 300W,
Bulb Shape	
Base Type	
Temperature Range	-30C to +60 C
Material	Aluminum and Toughened Glass
Lifespan	50,000 hours
Warranty	3 years
Size	
Dimensions	
Net Weight	
Certificates	
Certificates	cUL, CE, FCC, RoHS compliant
SKU	
100W 347V AC	SX-HB-100-347
150W 347V AC	SX-HB-150-347
200W 347V AC	SX-HB-200-347
300W 347V AC	SX-HB-300-347



Until recently, high-intensity discharge (HID) lighting systems were considered the only option for illuminating high-bay spaces.

Recent advances in LED lighting systems now make these systems more attractive choices for lighting spaces that have high ceilings.



kingers-supply.com

sales@kingers-supply.com

Box 1237 Three Hills, AB, T0M2A0

403-861-0033

BULBS FLOODS HIGHBAY PANEL LIGHTS RETROFIT STREET & PARKING LIGHTS VAPOR PROOF LIGHTS WALL PACK TUNNEL & CANOPY