

High-Bay GI Series

Replaces	HID lighting systems
Electrical	
Input Voltage	AC 100-277V
Frequency	50-60Hz
Power Factor	>0.95
Bulb Type	LED High Bay GI Series
Optical	
Lumens	9200 / 13100 / 17500 / 36800
CRI	>70
Beam Angle	90° or 110°
Mechanical	
Wattages	100W, 150W, 200W, 400W,
Bulb Shape	
Base Type	
Temperature Range	-30C to +60 C
Material	Aluminum, Copper Pipe, and Glass
Lifespan	50,000 hours
Warranty	5 years
Size	
Dimensions	14.7(L) x 14.7(W) x16.1”(H)
Net Weight	
Certificates	
Certificates	cUL, CE, FCC, RoHS compliant
SKU	
GI Highbay 100W	SX-GI-HB100
GI Highbay 150W	SX-GI-HB15
GI Highbay 200W	SX-GI-HB200
GI Highbay 400W	SX-GI-HB18



Meanwell UL / cUL Driver

Excellent heat sink with Copper Heart Pipe

IP 65 suitable for wet environments



kingers-supply.com

sales@kingers-supply.com

Box 1237 Three Hills, AB, T0M2A0

403-861-0033

BULBS FLOODS HIGHBAY PANEL LIGHTS RETROFIT STREET & PARKING LIGHTS VAPOR PROOF LIGHTS WALL PACK TUNNEL & CANOPY