





| Panel Lights 347VAC | |
|---------------------|----------------------------------|
| Replaces | Florescent 600x600x10mm 45W |
| - | Florescent 600x1200x13mm 70W |
| Electrical | |
| Input Voltage | 347Vac |
| Frequency | |
| Power Factor | |
| Bulb Type | LED, Dimmer purchased separately |
| Optical | |
| Color Temperature | 4000K |
| Lumens | 3645-3915 / 5810-6230 |
| CRI | |
| Beam Angle | 120° |
| Mechanical | |
| Wattages | 45W, 70W |
| Bulb Shape | |
| Base Type | |
| Temperature Range | -40C to +55 C |
| Material | Aluminum and Toughened Glass |
| Lifespan | 50-80,000 hours |
| Warranty | 5 years |
| Size | |
| Dimensions | 600x600x10mm / 600x1200x13mm |
| Net Weight | |
| Certificates | |
| Certificates | cUL, CE listed |
| SKU | |
| 45W | SX-PL-45 |
| 70W | SX-PL-70 |



LED panel lights with super bright SMD illumination provide better than 70% energy saving, over a 3 year life span.

No infrared rays, no ultraviolet radiation, no thermal effect, and soft and wide white light.

These recessed luminaires fit attractively into any kind of ceiling and can be applied to commercial, retail, and various other applications. Regardless of a need for exceptional uniform or more focused light, they all appear free of a visible light source.

SOLXLED luminaires provide the opportunity to transform general lighting into something special, a solution that combines efficient performance with ultra-smooth styling.

Replace or Retrofit for complete T8 or T5 Troffer. Mount on wall or ceiling, by suspending or replacing an existing troffer or tile.



kingers-supply.com